



MPO

400G BASE-SR16(CFP8 16*25G)
400G BASE-SR8(OSFP 8*50G)
400G BASE-SR8(QSFP-DD 8*50G)

16 32

400G

OM1 OM2 OM3 OM4 OM5 G652D G657A1 G657A2

OFNR OFNP LSZH

RoHS6.

连接器型号	插入损耗（平均值）	插入损耗（最大值）	回波损耗	单位
MPO(MM)	0.20	0.50	25	dB
MPO(SM)	0.30	0.70	50	dB

光缆芯数	16	32
最大安装拉力（N）	500	500
光缆最小弯曲半径静态（mm）	10	
光缆最小弯曲半径动态（mm）	20	
工作温度	-10 ~60 ()	
	-40 ~85 ()	

TIA/EIA-568-C.3

IEC 61754-7

GR-1435-CORE



OFC											
MT	MT	MT	MT	光纤类型	连接器类型	端面类型	扇出长度	光纤/缆	长度	极性	
4:4芯	8:8芯	16:16芯	32:32芯	S:G652 A2:G657A2 MT跳线	FC SC LC ST SMA	PC APC	0.5m 1m 2m 3m 5m 10m 15m 20m 30m 40m 50m 60m 70m 80m 90m 100m 120m 150m 200m 250m 300m 400m 500m 600m 700m 800m 900m 1000m 1200m 1500m 2000m 2500m 3000m 4000m 5000m 6000m 7000m 8000m 9000m 10000m	30:3mm光 45:4.5mm 75:7.5mm 120:12mm 150:15mm 200:20mm 250:25mm 300:30mm 400:40mm 500:50mm 600:60mm 700:70mm 800:80mm 900:90mm 1000:100mm 1200:120mm 1500:150mm 2000:200mm 2500:250mm 3000:300mm 4000:400mm 5000:500mm 6000:600mm 7000:700mm 8000:800mm 9000:900mm 10000:1000mm	A:直通型 B:完全交叉	OM3 OM4	